Appl No 10/011,860 Amdt. dated FEBRUARY 1, 2006 Reply to Office Action of November 1, 2005

Amendments to the Claims

+6123599349

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

- 1-48. (Cancelled).
- 49. (Currently Amended) A method for supplying power for anti-bradycardia pacing energy with an implantable cardioverter-defibrillator (ICD) comprising:

for subcutaneous subcutaneously positioning the ICD between the third rib and the twelfth rib of a patient;

[[and]] using a lead system that does not directly contact [[a]] the patient's heart or reside in the intrathoracic blood vessels and for providing to provide the anti-bradycardia pacing energy to the heart; the method comprising:

generating the anti-bradycardia pacing energy;

storing the anti-bradycardia pacing energy; and

delivering the anti-bradycardia pacing energy to the patient's heart;

wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a peak voltage that is between approximately 25 volts and approximately 50 volts.

- 50. (Previously Presented) The method of claim 55, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a peak voltage that is between approximately 1 volts and approximately 100 volts.
- 51. (Previously Presented) The method of claim 50, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a peak voltage that is between approximately .1 volts and approximately 25 volts.
- 52. (Previously Presented) The method of claim 50, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a peak voltage that is between approximately 25 volts and approximately 50 volts.

Appl No 10/011,860 Anidt, dated FEBRUARY 1, 2006 Reply to Office Action of November 1, 2005

FEB-01-06 15:18

53 (Currently Amended) A method for supplying power-for anti-bradycardia pacing energy with an implantable cardioverter-defibrillator (ICD) comprising:

+6123599349

for subcutaneous subcutaneously positioning the ICD between the third rib and the twelfth rib of a patient: [[and]]

using a lead system that does not directly contact [[a]] the patient's heart or reside in the intrathoracic blood vessels and for providing to provide the anti-bradycardia pacing energy to the heart; the method comprising:

generating anti-bradycardia pacing energy;

storing the anti-bradycardia pacing energy; and

delivering the anti-bradycardia pacing energy to the patient's heart;

wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a peak voltage that is between approximately 50 volts and approximately 75 volts.

54. (Cancelled)

55. (Currently Amended) A method for supplying power-for anti-bradycardia pacing energy with an implantable cardioverter-defibrillator (ICD) comprising:

for subcutaneous subcutaneously positioning the ICD between the third rib and the twelfth rib of a patient; [[and]]

using a lead system that does not directly contact [[a]] the patient's heart or reside in the intrathoracic blood vessels and for providing to provide the anti-bradycardia pacing energy to the heart; the method comprising:

generating anti-bradycardia pacing energy;

storing the anti-bradycardia pacing energy; and

delivering the anti-bradycardia pacing energy to the patient's heart;

wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a pulse width that is between 1 millisecond and approximately 40 milliseconds.

- 56. (Previously Presented) The method of claim 55, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a pulse width that is between approximately 2 milliseconds and approximately 10 milliseconds.
- 57. (Previously Presented) The method of claim 55, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a pulse width that is between approximately 10 milliseconds and approximately 20 milliseconds.
- 58. (Previously Presented) The method of claim 55, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a pulse width that is between approximately 20 milliseconds and approximately 30 milliseconds.
- 59. (Previously Presented) The method of claim 55, wherein the anti-bradycardia pacing energy comprises a monophasic waveform having a pulse width that is between approximately 30 milliseconds and approximately 40 milliseconds.
- 60. (Original) The method of claim 49, wherein the anti-bradycardia pacing energy comprises a monophasic waveform that is either positive or negative in polarity.
- 61. (Previously Presented) The method of claim 60, wherein the monophasic waveform has a tilt of between approximately 5% and approximately 95%.
 - 62. (Original) The method of claim 61, wherein the tilt is approximately 50%.
- 63. (Previously Presented) The method of claim 49, wherein the anti-bradycardia pacing energy comprises a monophasic waveform that is provided at a rate of between approximately 20 and approximately 120 stimuli/minute.
- 64. (Original) The method of claim 63, wherein the monophasic waveform is provided after a patient's heart rate is equal or less than approximately 20 beats/minute.

Appl. No. 10/011,860
Amdt. dated FEBRUARY 1, 2006
Reply to Office Action of November 1, 2005

- 65. (Original) The method of claim 49, wherein the implantable cardioverter-defibrillator is positioned subcutaneously between the third and fifth ribs.
- 66. (Original) The method of claim 49, wherein the implantable cardioverter-defibrillator is positioned subcutaneously between the fourth and sixth ribs.
- 67. (Original) The method of claim 49, wherein the implantable cardioverter-defibrillator is positioned subcutaneously between the sixth and eighth ribs.
- 68. (Original) The method of claim 49, wherein the implantable cardioverter-defibrillator is positioned subcutaneously between the eighth and tenth ribs.
- 69. (Original) The method of claim 49, wherein the implantable cardioverter-defibrillator is positioned subcutaneously between the tenth and twelfth ribs.